

DuploMED® 8411



Diagnostic



Electrodes



Wound Care



Surgical



Ostomy



Consumer
Healthcare



Wearables



Product construction

	Name	Colour	Thickness (mm)
Liner	Siliconized PE paper	white	approx. 0.12
Adhesive closed side	Pure acrylic copolymer	transparent	
Carrier	Polyester film	transparent	approx. 0.07
Adhesive open side	Pure acrylic copolymer	transparent	
Total thickness			approx. 0.19

Main application fields

- DuploMED® 8411 is used for the manufacturing of self-adhesive medical or technical devices.

Product advantages / Features and Benefits

- Good tack
- Skin friendly adhesive

Standard technical data

Shear strength *	on stainless steel at +23 °C ± 2°C	16	N/625 mm ²
Peel strength * 180°	on stainless steel at +23 °C ± 2°C	10-18	N/25 mm
Grammage	internal test method	77	g/m ²
Liner Release	internal test method	max. 0.3	N/25mm

* Test results are statistically approved.

DuploMED® 8411

Biocompatibility and safety

Customers should perform their own assessment to ensure the final product is in compliance with all applicable Medical Device regulatory requirements. To support the assessment, and upon request, Lohmann can provide, where available, biocompatibility testing results (ISO10993) specific to either the product supplied by Lohmann or its' constituent components.

Application condition

Recommended application temperature 18 °C to 35 °C

Application guidelines www.lohmann-tapes.com


Storage and shelf-life

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).
When properly stored the shelf-life of the product is at least 2 years after delivery.

Product presentation

Converted product	Rolls	Spools
Width [mm]	1000	
Length [m]	≤ 400	
Max. log width:	1000 mm	Other dimensions, die-cuts and sheets on request.


Sheet




Roll




Spool



Die Cut



Pick & Place



IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: August 2023